



Aquatainer™ 20L Collapsible - ICRC/IFRC Standard

Product key features

Aquatainer™ 20L Collapsible

- ICRC/IFRC Standard
- Collapsible 20L water container with handle for carrying and storing clean drinking water
- With or without spigot
- UV-stabilized and impact-resistant
- Can withstand temperatures between -20C to +50C
- Manufactured food grade low density polyethylene (LDPE) without toxic elements according to EN 1186-3-9 standards.

Technical specifications

Dimensions

Capacity	20L
Weight	265-275 g
Tap opening size	35 mm
Average thickness	0.60 mm and minimum corner thickness 0.50 mm
Built-in handle	90 x 30 mm
Polyamide string	1 mm diameter and 120 mm long

Materials

Marking and logo customised to your requirements.

Materials	
Container	Manufactured food grade LDPE without toxic elements according to EN 1186-3-9 standard
Operating temperature	Can withstand temperatures of -20C to +50C
Impact resistance / drop test	Impact resistant on hard surface when filled with maximum volume of 20L water. Needs to complete testing of 10 consecutive drops from a 2.00m height, filled with water to its normal maximum capacity. To be accepted, the water container must resist to a minimum of 3 drops
Color	Translucent, UV-stabilized

Packing & shipping

Content	30 pcs per carton	Estimated loadability ¹		
Weight per carton	12.7 kg	Container	With pallet	Without pallet
Dimension per carton	64 x 40 x 51 cm	20' GP container	22 pallets (3,960 pcs)	192 cartons (6,120 pcs)
Volume per carton	0.13 cbm	40' GP container	48 pallets (8,640 pcs)	392 cartons (12,240 pcs)
Carton per pallet	6 cartons	40' HC container	48 pallets (8,640 pcs)	490 cartons (14,850 pcs)
Weight per pallet	98.4 kg			
Dimension per pallet	120 x 80 x 114 cm			
Volume per pallet	1.0944 cbm			

¹ The loadability provided is based on the maximum volume and weight capacity of the containers. This might change due to road weight restrictions in the country of destination. Please contact our sales team for further clarifications.