



Aquatainer™ 20L Collapsible - ICRC/IFRC Standard

Product key features

Aquatainer™ 20L Collapsible

- ICRC/IFRC Standard
- Collapsible 20L water container with handle for carrying and storing clean drinking water
- With or without spigot
- UV-stabilized and impact-resistant
- Can withstand temperatures between -20C to +50C
- Manufactured food grade low density polyethylene (LDPE) without toxic elements according to EN 1186-3-9 standards.

Technical specifications

Dimensions

Capacity	20L
Weight	265-275 g
Tap opening size	35 mm
Average thickness	0.60 mm and minimum corner thickness 0.50 mm
Built-in handle	90 x 30 mm
Polyamide string	1 mm diameter and 120 mm long

Materials

Marking and logo customised to your requirements.

Materials	
Container	Manufactured food grade LDPE without toxic elements according to EN 1186-3-9 standard
Operating temperature	Can withstand temperatures of -20C to +50C
Impact resistance / drop test	Impact resistant on hard surface when filled with maximum volume of 20L water. Needs to complete testing of 10 consecutive drops from a 2.00m height, filled with water to its normal maximum capacity. To be accepted, the water container must resist to a minimum of 3 drops
Color	Translucent, UV-stabilized

Packing & shipping

Content	30 pcs per carton
Weight per carton	12.50 kg approx.
Dimension per carton	64 x 40 x 51 cm
Volume per carton	0.13 cbm approx.
Carton per pallet	8 cartons (240 pcs)
Weight per pallet	118 kg approx.
Dimension per pallet	136 x 88 x 115 cm
Volume per pallet	1.376 cbm approx.

Estimated loadability ¹		
Container	With pallet	Without pallet
20' GP container	4,800 pcs	6,120 pcs
40' GP container	10,080 pcs	12,240 pcs
40' HC container	10,080 pcs	14,850 pcs

¹ The loadability provided is based on the maximum volume and weight capacity of the containers. This might change due to road weight restrictions in the country of destination. Please contact our sales team for further clarifications.