



Huggy Pro - HPT 48

High Performance Tent - UNICEF Standard



Fire retardant



Waterproof



UV stabilised



All climate zones



› Key Features

- » Huggy Pro - High Performance Multipurpose Tent is made of high quality and durable materials, ensuring a strong construction.
- » Comprises an outer cover, shade net, groundsheet, and partition as its solution.
- » Offers a spacious 48 m² tent with vertical walls for optimum use of inner space.
- » Presents cost-efficient, lightweight, and compact packing.
- » Utilises a strong and lightweight high tensile steel frame structure to withstand high wind and snow loads.
- » Allows easy cleaning and disinfection, resisting commonly used disinfectants and detergents, and prevents mildew.
- » Performs highly in hot, cold, and wet weather conditions; does not 'heat up' in direct sunlight, blocks UV, and neither breaks nor absorbs moisture in below-zero temperatures.
- » Provides high comfort thanks to advanced ventilation and large mesh windows.
- » Incorporates environmental considerations with a low energy production process, full recyclability, and safe disposal by burning or burying when recycling is not possible.

› Dimensions


Total size	48 m ²
Floor size	6.0 x 8.0 m (±1%)
Central height outer tent	3.00 m (±1%)
Wall height outer tent	2.05 m (±1%)
Structure	Lightweight tubular steel frame structure
Window size	135 x 135 cm
Ventilation grates	135 x 20 cm

Add-ons

- » Patient liner
- » Inner liner
- » Winter liner with insulated flooring
- » Hard flooring
- » Electrical lighting kit
- » Solar lighting kit

› Graphic Reference

Front view



Side view (Window and ventilation)



Top view


NRSRelief
www.nrsrelief.com



Huggy Pro - HPT 48

High Performance Tent - UNICEF Standard



Fire retardant



Waterproof



UV stabilised



All climate zones

› Materials

Outer liner and mud flaps	250 g/m ² ±10% HDPE/LDPE laminated woven fabric, waterproof 5,000 mm, UV resistant, fire retardant CPAI 84 (sections 5 and 6) 30 seconds and durable
Ground sheet	190 g/m ² ±10% HDPE/LDPE laminated woven fabric, waterproof 5,000 mm, fire retardant CPAI 84 (sections 5 and 6) 30 seconds and durable
Shade net	190 g/m ² ±10% HDPE knitted mesh, UV-resistant, fire retardant CPAI 84 (sections 5 and 6) 30 seconds 10x guy rope PP 4.5 m / 10 mm Ø with reflective stripes and 'glow-in-the-dark' PE tensioner
PES mesh, PVC coated, for windows and ventilation grates	195 g/m ² ±10% PVC coated PES knitted mesh, UV resistant and fire retardant Din 75200
Steel tubing for frame	Steel quality: high tensile steel, quality Q195, rolled and welded tubing, electrolytic galvanised Diameter 38 mm, wall thickness 1.5 mm. Frame components are powder coated after fabrication
Partitioning kit	190 g/m ² ±10% HDPE/LDPE laminated woven fabric, waterproof 5,000 mm, UV resistant, fire retardant CPAI 84 (sections 5 and 6) 30 seconds and durable. Attached to frame or inner liner with toggles/loops. Overlapping door in centre with toggle/loop closure. Dimensions 600 cm x 210 cm (wall) / 300 cm (centre)
Master bags	PVC 450 g/m ² , waterproof 10,000 mm
Carry bags	Polyethylene HDPE/LDPE laminated woven fabric, waterproof 5,000 mm, fire retardant CPAI 84 (sections 5 and 6) 30 seconds and durable
Doors	Polyethylene material. Centre door: 120 x 200 cm, side doors 150 x 200 cm. Closing by strong block zippers, with buckle closures as back up in case of failure. Mosquito net doors: 80 g/m ² polyester mesh
Accessories	» 10x T-stakes – 50 x 25/3 mm / 40 cm » 36x Lollypop pegs - 8 mm Ø 30 cm » 10 + 4 Twisted spikes - 20 mm Ø 60 cm » 8x Flathead spikes – 10 mm Ø 40 cm » 2x Candy cane pegs - 10 mm Ø 30 cm (canopy kit) » 10x guy rope PP 4.5 m / 10 mm Ø with reflective stripes and 'glow-in-the-dark' PE tensioner
Repair kit	Patches of all fabrics, needles and tread, duct tape, zipper puller, buckles, rope, runners, webbing, repair instruction, packed in marked pouch with hanging loops
Colours	White outer liner, light grey groundsheet, black trimmings

› Packing and Shipping - Bags/Cages

Main tent, carry bags


Carry bags	Contents	Dimensions (cm)	Volume (m ³)	Weight (kg)	Packing unit
1/10	1x Manual 1x Alignment straps 8x Bottom pipe 195 cm 10x Stand poles with base plate 166 cm 6x Extension pole 34 cm	200 x 35 x 15	0.105	44.35	1/3 Master Bag 
2/10	10x Roof poles 220 cm	220 x 22 x 8	0.039	24.75	
3/10	12x Purlin 185 cm	186 x 20 x 11	0.041	24.55	
4/10	10x Eave joint 5x Ridge joint 4x Bracing cable	220 x 60 x 30	0.396	37.30	2/3 Master Bag 
5/10	1x Outer cover including 10 guy lines and runner	222 x 180 x 10	0.399	53.45	
6/10	1x Ground sheet 1x Partitioning kit 2x Gable end cover	220 x 180 x 10	0.396	36.1	


NRSRelief
www.nrsrelief.com




Huggy Pro - HPT 48


High Performance Tent - UNICEF Standard




Fire retardant



Waterproof



UV stabilised



All climate zones

› Packing and Shipping - Bags/Cages

Main tent, carry bags

Carry bags	Contents	Dimensions (cm)	Volume (m³)	Weight (kg)	Packing unit
7/10	1x Shade net cover (10 guy lines and runner) 1x Shade net frame complete set	210 x 50 x 20	0.210	45.45	3/3 Master Bag 
8/10	Accessories 10x T-Stake 40 cm 36x Lollypop peg 30 cm 10x Twisted spike 60 cm 1x Hammer	100 x 20 x 12	0.024	30.10	
9/10	2x H-Frame Kit 8x Flathead spikes 40 cm 4x Twisted spike 60 cm Canopy Kit 2x Standing pole 2x Guy ropes with runner of 4 m 2x Candy cane peg 30 cm	220 x 25 x 15	0.066	30.55	
10/10	Repair Kit 1m Mesh fabric 2m P.E fabric 2m P.E ground sheet 2m PVC film 2m Shade net fabric 3x Strong needles 1x Roll of sewing thread 1x Roll of duct tape white 5m x 50mm 2x Spare zipper sliders 2x Tension lock 25 mm 4x Tension lock 40 mm 4m Webbing 25 mm 4m Webbing 40 mm 10x Plastic toggle 1.5m Velcro male/female 25 mm 10m Guy rope 8 mm 3x Guy rope tensioner 8 mm 8x Pin lock 8x Hitch pin 4x Buckle male/female 25	115 x 35 x 7	0.028	5.2	

› Details of Packing Unit


Item name	Packing unit	Content of master bag	Dimensions of master bag (cm)	Volume of master bag (m³)	Weight of master bag (kg)
Frame tent with standard liner	Master Bag 1	Carry bags 1/10, 2/10 and 3/10	222 x 45 x 23	0.229	95.75 ±5%
	Master Bag 2	Carry bags 4/10, 5/10 and 6/10	222 x 65 x 45	0.649	132.30 ±5%
	Master Bag 3	Carry bags 7/10, 8/10, 9/10 and 10/10	222 x 50 x 30	0.333	113.80 ±5%
	Total			1.211 approx.	341.85 ±5%


NRSRelief
www.nrsrelief.com




Huggy Pro - HPT 48


High Performance Tent - UNICEF Standard




Fire retardant



Waterproof



UV stabilised



All climate zones

› Estimated Loadability

Item name	Custom Cages	Standard Cages
Item name	Frame tent with standard liner	Frame tent with standard liner
Dimensions of loaded cage	222 x 70 x 113 cm	222 x 92 x 113 cm
Volume of loaded cage	1.756 m ³	2.308 m ³
Quantity per cage	1 tent	2 tents
Weight of 1x loaded cage	372 kg ±5%	716 kg ±5%

Photos



› Quantity

Item name		20' GP	40' DC	40'HC
Frame tent with standard liner	Standard cage	24	52	52
	Custom cage	16	34	34

› Stackability

Standard cage 3x steel cages (6 x 48m² tents), height will be approx. 3.40 m

Custom cage (one tent per cage) 3x steel cages, height will be approx. 3.40 m

i For storage purposes, the cages can be stacked 3 cages high.
Be sure to place the cages on a solid floor, or place wooden planks or concrete tiles under the feet of the cages when placed on soft ground.


NRSRelief
www.nrsrelief.com